

60,130-1342  
OOMRA0381

**IN THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**OFFICIAL**

**Listing of Claims:**

1. (Currently Amended) An assembly including:  
a first, second and third components and first and second fixing members, the first, second and third components having respective first, second and third holes, the first hole being a threaded hole, in which the first fixing member extends through the second hole and a first threaded portion of the first fixing member engaging the first hole to secure the first component to the second component, at least one of the fixing members extending through the third hole with the first fixing member engaging the second fixing member to secure the third component to the first component, and the first component being situated between the second and third component wherein the first component is a door panel, the second component is a window regulator mechanism and the third component is a window regulator drive system.
2. (Previously Presented) The assembly according to Claim 1 in which a first feature on the first component engages a first feature on the second component to align the first component relative to the second component.
3. (Previously Presented) The assembly according to Claim 1 in which the second component has a first surface for engagement with the first fixing member to align the second component relative to the first component.
4. (Previously Presented) The assembly according to Claim 1 in which a first feature on the third component engages a second feature of the first component to align the first component relative to the third component.

**RECEIVED  
CENTRAL FAX CENTER**

**SEP 16 2003**

60,130-1342  
OOMRA0381

5. (Previously Presented) The assembly according to Claim 2 in which the first feature of at least one of the components is a recess.

6. (Previously Presented) The assembly according to Claim 2 in which the first feature of at least one of the components is a projection.

7. (Previously Presented) The assembly according to Claim 4 in which at least one of the first feature of the third component and the second feature of the first component is a recess.

8. (Previously Presented) The assembly according to Claim 4 in which at least one of the first feature of the third component and the second feature of the first component is a projection.

9. (Previously Presented) The assembly according to Claim 2 in which at least one of the first feature of the first component and the first feature of the second component is contiguous with at least one of the holes.

10. (Previously Presented) The assembly according to Claim 4 in which at least one of the first feature of the third component and the second feature of the first component is contiguous with at least one of the holes.

11. (Previously Presented) The assembly according to Claim 2 in which a first feature on the third component engages a second feature of the first component to align the first component relative to the third component and the first and second features of the first component are on opposite sides of the first component and are aligned.

12. (Previously Presented) The assembly according to Claim 9 in which the first feature of the first component is at least one of a recess and a projection and the second feature of the first component is at least one of a recess and projection.

60,130-1342  
OOMRA0381

13. (Previously Presented) The assembly according to Claim 10 in which the first component is made from metal, with the first hole being at least partially formed by a pressing operation and with the first and second features being at least partially formed by a pressing operation.

14. (Previously Presented) The assembly according to Claim 1 in which the third component has a first surface for engagement with at least one of the first and second fixing members to align the third component relative to at least one of the first and second components.

15. (Previously Presented) The assembly according to Claim 1 in which the first component is sealed relative to the second component and the first component is sealed relative to the third component.

16. (Previously Presented) The assembly according to Claim 1 designed such that forces acting on the first fixing member prevents rotation of the first fixing member relative to the first component during securing and releasing of the third component by the second fixing member.

17. (Currently Amended) ~~The assembly according to Claim 1 in which~~ An assembly including:

a first, second and third components and first and second fixing members, the first, second and third components having respective first, second and third holes, the first hole being a threaded hole, in which the first fixing member extends through the second hole and a first threaded portion of the first fixing member engaging the first hole to secure the first component to the second component, at least one of the fixing members extending through the third hole with the first fixing member engaging the second fixing member to secure the third component to the first component, and the first component being situated between the second and third component wherein the first threaded portion has a diameter which is greater than the diameter of a second threaded portion.

60,130-1342  
OOMRA0381

18. (Currently Amended) ~~The assembly according to Claim 1 in which~~ An assembly including:

a first, second and third components and first and second fixing members, the first, second and third components having respective first, second and third holes, the first hole being a threaded hole, in which the first fixing member extends through the second hole and a first threaded portion of the first fixing member engaging the first hole to secure the first component to the second component, at least one of the fixing members extending through the third hole with the first fixing member engaging the second fixing member to secure the third component to the first component, and the first component being situated between the second and third component wherein the first threaded portion has a pitch which is different from the pitch of the first hole, and the second threaded portion has a pitch which is substantially equal to the pitch of the second fixing member.

19-21. (Cancelled).

60,130-1342  
OOMRA0381

22. (Currently Amended) ~~The method of assembly of a door assembly according to~~  
~~claim 19~~ A method of assembly of a door assembly comprising the steps of:  
providing a first, second and third components and a first and second fixing  
members, the first, second and third components having respective first, second and third  
holes, the first hole being a threaded hole;  
assembling the first and second components and first fixing member to form a  
subassembly such that the first fixing member extends through the second hole and a first  
threaded portion of the first fixing member engages the first hole to secure the first  
component to the second component;  
then assembling the third component to the subassembly; and  
then mounting the second fixing member on the first fixing member with the first  
fixing member engaging the second fixing member to secure the third component to the  
first component to form an assembly such that at least one of the fixing members extends  
through the third hole in which the first component is situated between the second and  
third component wherein the first component is a door panel, the second component is a  
window regulator mechanism and the third component is a window regulator drive  
system.

60,130-1342  
OOMRA0381

\_\_\_\_ 23. (Currently Amended) ~~The method of maintaining an assembly according to claim 20~~ A method of maintaining an assembly comprising the steps of:

providing a first, second and third components and a first and second fixing members, the first, second and third components having respective first, second and third holes, the first hole being threaded, in which the first fixing member extends through the second hole and a first threaded portion of the first fixing member engaging the first hole to secure the first component to the second component, at least one of the fixing members extending through the third hole, and with the first fixing member engaging the second fixing member to secure the third component to the first component, and the first component being situated between the second and third component;

removing the second fixing member;

removing the third component;

replacing the third component; and

replacing the second fixing member wherein the first component is a door panel, the second component is a window regulator mechanism and the third component is a window regulator drive system.

24-25. (Cancelled)

26. (Previously Presented) The assembly according to claim 1 wherein the first hole is pre-threaded.

27. (Currently Amended) The assembly according to claim 1 wherein the ~~first component is a door module, the second component is a window regulator mechanism and the third component is a window regulator drive system~~ door panel is a door module.

28. (Cancelled)